



WÓZKI WIDŁOWE ELEKTRYCZNE GOODSENSE ELECTRIC FORKLIFT

Specyfikacja

Power source		Battery	Battery	Battery	Battery
Rated load capacity	kg	4000	4500	5000	6000
Load centre	mm	500	500	500	500
Lift height	mm	3000	3000	3000	3000
Fork size (LxWxT)	mm	1070x150x50	1070x150x50	1070x150x50	1070x150x50
Fork carriage tilt(F/R)	°	6°/9°	6°/9°	6°/9°	6°/9°
Overall Length(to fork face)	mm	3030	3030	3030	3030
Overall Width	mm	1600	1600	1600	1600
Mast Lowered Height	mm	2330	2330	2330	2330
Mast Extended Height	mm	4255	4255	4255	4255
Overhead Guard Height	mm	2255	2255	2255	2255
Wheelbase	mm	2000	2000	2000	2000
Overall length(with forks)	mm	4100	4100	4100	4100
Gradeability(Laden)	%	15	15	15	15
Front Tire		28x12.5-15-24PR	28x12.5-15-24PR	28x12.5-15-24PR	28x12.5-15-24PR
Rear Tire		7.0-12-14PR	7.0-12-14PR	7.0-12-14PR	7.0-12-14PR
Battery(Voltage/Capacity)	V/Ah	80/700	80/700	80/700	80/800
Drive motor	Kw	2x11	2x11	2x11	2x11
Lifte motor	Kw	26	26	26	26