



WÓZKI WIDŁOWE GAZOWE GOODSENSE FY50/FY60/FY70

Specyfikacja

	1	Model		FY50	FY60	FY70	
General	2	Power type		LPG	LPG	LPG	
	3	Rated Capacity	kg	5000	6000	7000	
	4	Load centre	mm	600	600	600	
	5	Lift Height	mm	3000	3000	3000	
	6	Fork Size	LxWxT	mm	1220x150x60	1220x150x60	1220x150x70
	7	Mast title Angle	F/R	Deg	6°/12°	6°/12°	6°/12°
	8	Front Overhang (Wheel center to fork face)		mm	590	590	595
	9	Ground clearance (Bottom of mast)		mm	200	200	200
	Characteristic&Dimension	10		Length to face of fork (without fork)	mm	3450	3450
11			Overall width	mm	2010	2010	2010
12		Overall Dimension	Mast Lowered Height	mm	2550	2550	2550
13			Mast Extended Height (with backrest)	mm	4380	4380	4380
14			Overhead Guard Height	mm	2470	2470	2470
15		Turning Radius (outside)		mm	3250	3250	3350
16		Min. intersecting aisle		mm	2960	2960	3040
Performance	17	Speed	Travel(no load)	km/h	30	30	30
	18		Lifting(full load)	mm/s	500	500	460
	19	Max Gradeability		%	20	20	20
	Chassis	20	Tire	Front		8.25-15-14 PR	8.25-15-14 PR
21		Rear			8.25-15-14 PR	8.25-15-14 PR	8.25-15-14 PR
22		Wheelbase	mm	2250	2250	2250	
23		Service Weight	kg	8550	9150	9750	
Power&Transmission	24	Battery	Voltage/Capacity	V/Ah	(12V/80AH) × 2	(12V/80AH) × 2	(12V/80AH) × 2
	25	Engine	Model		GM4.3L		
	26		Manufacture		GM		
	27		Rated output/r.p.m.	kwt/r.p.m	56/2200		
	28		Rated torque/r.p.m.	N-mt/r.p.m	240/750		
	29		No.of Cylinder		6		
	30		BorexStroke	mm	101.6x88.39		
	31		Displacement	cc	4300		
	32	Fuel Tank Capacity	L	140	140	140	
	33	Transmission	Type		Hydraulic	Hydraulic	Hydraulic
	34		Stage FWD/RVS		2/2	2/2	2/2
35	Operating pressure for attachment		Mpa	19	19	19	