



# WÓZKI WIDŁOWE SPALINOWE GOODSENSE FD10/FD15/FD18

## Specyfikacja

Type of model		FD10	FD15	FD18
Power source		Diesel	Diesel	Diesel
Rated load capacity	kg	1000	1500	1800
Load centre	mm	500	500	500
Lift height	mm	3000	3000	3000
Fork size (LxWxT)	mm	920x120x35	920x120x35	920x120x35
Fork carriage tilt(F/R)	°	6°/12°	6°/12°	6°/12°
Overall Length(Length to fork face)	mm	2205	2285	2285
Overall Width	mm	1086	1086	1086
Mast Extended Height	mm	3940	3940	3940
Mast Lowered Height	mm	1995	1995	1995
Overhead Guard Height	mm	2040	2040	2040
Gradeability(Laden)	%	20	20	20
Front Tire		6.50-10-10PR	6.50-10-10PR	6.50-10-10PR
Rear Tire		5.00-8-10PR	5.00-8-10PR	5.00-8-10PR

## Silnik

Brand		ISUZU	XINCHAI	XINCHAI
Model		C240PKJ	NB485BPG-7	NC485BPG-508
Rated output	kw/r.p.m	35.4/2500	30/2600	30/2600
Rated torque	Nm/r.p.m	139/1800	131/1700-1900	131/1700-1900
No. of cylinder		4	4	4
Bore x Stroke	mm	86X102	85X100	85X100
Displacement	cc	2369	2270	2270
		ISUZU	XINCHAI	XINCHAI
Model		C240PKJ	NB485BPG-7	NC485BPG-508
Rated output	kw/r.p.m	35.4/2500	30/2600	30/2600
Rated torque	Nm/r.p.m	139/1800	131/1700-1900	131/1700-1900
No. of cylinder		4	4	4
Bore x Stroke	mm	86X102	85X100	85X100
Displacement	cc	2369	2270	2270