



# WÓZKI WIDŁOWE SPALINOWE GOODSENSE FD40/FD45/FD50

## Specyfikacja

Type of model		FD40	FD45	FD50(small)
Power source		Diesel	Diesel	Diesel
Rated load capacity	kg	4000	4500	5000
Load centre	mm	500	500	500
Lift height	mm	3000	3000	3000
Fork size (LxWxT)	mm	1070x150x50	1070x150x50	1070x150x50
Fork carriage tilt(F/R)	°	6°/12°	6°/12°	6°/12°
Overall Length(Length to face of fork)	mm	3220	3220	3220
Overall Width	mm	1480	1480	1480
Mast Lowered Height	mm	2330	2330	2330
Mast Extended Height	mm	4250	4250	4250
Overhead Guard Height	mm	2320	2320	2320
Gradeability(Laden)	%	20	20	20
Front Tire		300-15-18PR	300-15-18PR	300-15-18PR
Rear Tire		7.00-12-12PR	7.00-12-12PR	7.00-12-12PR

## Silnik

Brand		PERKINS	WEIFANG	LUOTUO
Model		1104D-44	R4105G32	LR4B3-G89X6-U2
Rated output	kw/r.p.m	56/2200	59/2400	57/2200
Rated torque	Nm/r.p.m	260/1900	270/1600-1800	284-297/1400-1600
No. of cylinder		4	4	4
Bore x Stroke	mm	105X127	105X125	108X125
Displacement	cc	4400	4330	4578